

YEAR 2020









S.I.V.I.T. Srl

The company was created in 2011 from a pool of professionals, highly customer oriented for small, medium and large companies.

We offer an innovative and multi-purpose use, ranging in various fields (such as chemical, petrochemical, food industry, gas lines etc.).



All the precision activities are executed in our workshops.

General machining are carried out by certified medium and small enterprises located very close to S.I.V.I.T. plant.

This choice was taken to supervise the production process and reduce as much as possible the environment's impact with the aim to encourage and promote Italian production, empathize the European quality and products excellence.




SIZES AND RATINGS

Sizes from 2"/DN 50 up to 24"/DN 600 (Bigger sizes available upon request).

Available Ratings:

PN 10/16/25/40

ANSI 150/300 (600 upon request)




CENTRIC



LINED WORKING PRINCIPLES Class Ansi 150 PN 10/16


The rotation axe match all themain components, Body valve, Seat sleeve, and disc. The zero leakage is guarantee by the interference between disc and seat.



The Centric (lined) type butterfly are realized in special material for heavy duty application, sleeve available in Viton, NBR, EPDM and PTFE.
Hydraulic, pneumatic or electric actuatoravailable upon request.


TOP MOUNTING

Shaft coupling depending on customer's requirements and it may be realized in different configuration than those shown. Flanges inaccording with ISO 5211.






≤







VALVE DIMENSION



Dimensions are in mm, the data migth change, S.I.V.I.T Srl reserves the right to make changes or technical improvements without prior notice.

DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L1	54	72	82	92	102	120	133	166	201	234	268	299	355	393	464
L2	13	135	150	160	180	195	210	240	279	315	330	365	397	437	522
L3	33	43	46	46	52	56	56	60	68	78	80	102	113	126	153

TORQUE VALUES


D	N	Breakaway torque (Nm)
40	11/2	35
50	2″	35
65	21/2	40
80	3″	40
100	4"	50
125	5″	62
150	6"	94
200	8″	209
250	10"	242
300	12"	308
350	14"	500
400	16"	600
450	18"	800
500	20"	1200
600	24"	1900

The torque values in the above table are in Nm.

FLANGE BOLTING DIMENSION

	DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600
9	FF	33	43	46	46	52	56	56	60	68	78	78	102	114	127	154
Z	ØL	100	110	130	150	170	200	225	280	335	395	445	495	550	600	705
Р	NxØ	4*Ø14	4*Ø14	4*Ø14	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø22	4*Ø22	4*Ø22	4*Ø22	4*Ø22	4*Ø26
	NxM	4*M12	4*M12	4*M12	4*M16	4*M16	8*M16	8*M16	8*M16	12*M16	12*M20	12*M20	16*M20	16*M20	20*M20	20*M24
	DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600
10	FF	33	43	46	46	52	56	56	60	68	78	78	102	114	127	154
Z	ØL	110	125	154	160	180	210	240	195	350	400	460	515	565	620	725
Ы	NxØ	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø22	4*Ø22	4*Ø22	4*Ø22	4*Ø22	4*Ø26	4*Ø26	4*Ø26	4*Ø30
1	NxM	4*M16	4*M16	8*M16	8*M16	8*M16	8*M16	8*M20	8*M20	12*M20	12*M20	16*M20	16*M24	20*M24	20*M24	20*M27
	DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600
16	FF	33	43	46	46	52	56	56	60	68	78	78	102	114	127	154
Z	ØL	110	125	145	160	180	210	240	295	355	410	470	525	585	650	770
Б	NxØ	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø22	4*Ø22	4*Ø26	4*Ø26	4*Ø26	4*Ø30	4*Ø30	4*Ø33	4*Ø33
	NxM	4*M16	8*M16	8*M16	8*MM16	8*M16	8*M16	8*M20	12*M20	12*M24	12*M24	16*M24	16*M27	20*M27	20*M30	20*M33
	DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600
0	FF	33	43	46	46	52	56	56	60	68	78	78	102	114	127	154
15	ØL	114,3	120,7	139,7	152,4	190,5	215,9	241,3	298,5	362	431,8	476,3	539,8	577,9	635	749,3
#	NxØ	4*7/8"	4*3/4"	4*3/4"	4*3/4"	4*3/4"	4*7/8"	4*7/8"	4*7/8"	4*1"	4*1"	4*1" 1/8	4*1"1/8	4*1"1/4	4*1"1/4	4*1"3/8
	NxM	4*3/4"	4*5/8"	4*5/8"	4*5/8"	8*5/8"	8*3/4"	8*3/4"	8*3/4"	12*7/8"	12*7/8"	12*1"	16*1"	16*1"1/8	20*1"1/8	20*1"1/8
	NxM	4*3/4"	4*5/8"	4*5/8"	4*5/8"	8*5/8"	8*3/4"	8*3/4"	8*3/4"	12*7/8"	12*7/8"	12*1"	16*1"	16*1"1/8	20*1"1/8	20

Kv VALUE (m³/h)



The flow factor "Kv" is defined as the flow of water, through a valve at temperatures between 5-40 °C, in cubic meters per hour (m³/h) at a pressure drop of 1 bar. This factor depends on the diameter of the valve, the shutter angle of aperture and its design.


$\overline{}$	20°	30°	40°	50°	60°	70°	80°	90°
40		2,7	8,5	16	25	37	46	50
50	2	7	15	28	45	68	88	100
65	3	11	24	48	85	138	180	210
80	8	22	50	83	134	230	312	360
100	15	35	70	130	225	410	585	650
125	28	70	135	230	360	600	920	1050
150	33	95	205	320	580	980	1410	1620
200	60	175	355	580	910	1600	2450	2800
250	132	340	590	940	1480	2550	3950	4480
300	200	505	890	1450	2100	3800	5960	6800
350	280	680	1200	2050	3150	5050	8100	9200
400	365	860	1500	2490	3980	6600	10200	11700
450	465	1080	1900	3150	5050	8700	13300	15200
500	580	1200	2300	3740	6150	11000	16800	18900
600	820	1600	2780	5200	8940	14500	23500	26800





GENERAL INFORMATION Class Ansi 150/300 PN 16/25/40

- Interception (ON OFF) and regulation of gaseous media and liquid
- Curve flow almost equivalent percentage (almost a full bore)
- Double eccentric disc and shaft
- No maintenance required
- Long life even under the most critical conditions



TOP MOUNTING

Shaft finished depending on the requirements of implementing, on request may be made different than those shown above. Flanges in according with ISO 5211.

DOUBLE OFFSET




The solution to double eccentricity has the advantage of the "perfect seal", and thanks to the interchangeability of the seals, they are perfectly adapted to the major areas of application.

TORQUE extremely reduced in the drive.

4 DIFFERENT SEATS TYPE TO COVER ALL THE MAIN APPLICATION


SOFT SEAT

(NBR, EPDM, FKM, PTFE, RPTFE)




SOFT SEAT with FIRESAFE Ring

(NBR, EPDM, FKM, PTFE, RPTFE)



Once destroyed the seal, the firesafe ring tends to bend under the pressure of the retaining ring and the seal is assured up to the time of the next maintenane METAL SEAT (Helicoflex)




N.B. The valves are designed and tested bidirectionally, but for their design double offset recommend a preferential flow direction for maximum efficiency.


SS SIVIT STANDARD TYPE





8 8	PARTS LIST
POS.	DESCRIPTION
1	BODY
2	RING
3	SELF- LUBRIFICATING
	BEARING
4	RING NUT
5	RENFORCED SEALING RING
6	DISK
7	STEM
8	SELF- LUBRIFICATING BEARING
9	RING
10	SPLIT RINGS
11	BLIND PLUG
12	FLANGE
13	PIN
14	SCREW







	PARTS LIST
POS.	DESCRIPTION
	BODY
2	DISC
3	STEM
4	BLINDPLUG
4 5 7	SOFT SEAT
	UPPER BUSHING
	LOWER BUSHING
9	UPPER PACKING
10	ANTIBLOWOUT
10.1	SCREW (ANTIBLOWOUT)
10.2	SPIRAL WOUND GASKET
	(ANTIBLOWOUT)
11	ÎD PLATE
	RIVET
	RETAINING RING
15	SOCKET HEAD CAP SCREW
	(BLIND PLUG)
16	SOCKET HEAD CAP SCREW
	(RET. RING)
	PIN (DISC/STEM)
	GLANDPLUG
	STUD (GLANDPLUG)
	HEX. NUT (GLANDPLUG)
21	WASHER (GLANDPLUG)
	ANTI-STATIC SPRING
	ANTI-STATIC BALL
24	SPIRAL WOUND GASKET
	(BLINDPLUG)
	HEX. BOLT (BRACKET)
26	WASHER (BRACKET)
27	BRACKET
28	HEX. BOLT (COMMAND)
	WASHER (COMMAND)
30	HAND LEVER
	FIRESAFE RING
	SPIRAL WOUND GASKET
	(RET. RING)




SF FUGITIVE EMISSION TYPE &




	PARTS LIST
POS.	DESCRIPTION
1	BODY
2	DISC
3	STEM
2 3 4 5 7	BLIND PLUG
5	SOFTSEAT
	UPPER BEARING
8	LOWER BEARING
9	UPPER PACKING
10	ANTI-BLOWOUT DEVICE
11	ID PLATE
12	RIVET
14	RETAINING RING
15	SOCKET HEAD CAP SCREW
	(BLIND PLUG)
16	SOCKET HEAD CAP SCREW
	(RET. RING)
17	HEX. BOLT (GLAND PLUG)
18	KEY
19	GLAND PLUG
20	STUD (GLAND PLUG)
21	WASHER (GLAND PLUG)
22	ANTI-STATIC SPRING
23	ANTI-STATIC BALL
24	SPIRAL WOUND GASKET
	(BLIND PLUG)
25	LOWER BUSHING
26	WASHER (BRACKET)
27	BRACKET
28	HEX. BOLT (COMMAND)
29	WASHER (COMMAND)
30	COMMAND





VALVE DIMENSION

Dimensions are in mm, the data migth change, S.I.V.I.T Srl reserves the right to make changes or technical improvements without prior notice.




150	DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
80,48,60	L1	100	105	125	150	165	185	215	240	285	300	340	380	410	495
ASME	L2	165	175	180	210	245	260	290	335	370	400	470	500	570	650
A	L3	25	25	25	30	30	40	45	45	60	60	75	75	90	100
300	DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
	L1	110	125	150	160	180	195	235	260	300	330	370	400	445	525
ASME	L2	170	180	195	220	260	280	300	345	380	425	500	530	590	660
A	L3	25	25	25	30	30	40	45	45	60	60	75	75	90	120
009	DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
73/6/75/	L1	120	140	165	180	215	220	260	300	335	390	415	450	490	565
ASME	L2	185	200	215	240	280	300	325	370	400	460	525	560	600	675
Ā	L3	35	35	35	40	40	50	60	60	75	75	90	90	120	150

FLANGE BOLTING DIMENSION

	DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
16	FF	43	46	46	52	56	56	60	68	78	78	102	114	127	154
	ØL	125	145	160	180	210	240	295	355	410	470	525	585	650	770
P N	NxØ	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø18	4*Ø22	4*Ø22	4*Ø26	4*Ø26	4*Ø26	4*Ø30	4*Ø30	4*Ø33	4*Ø33
	NxM	8*M16	8*M16	8*MM16	8*M16	8*M16	8*M20	12*M20	12*M24	12*M24	16*M24	16*M27	20*M27	20*M30	20*M33
	DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
2	FF	43	46	48	54	59	59	73	83	92	117	133	149	159	181
PN2	ØL	125	145	160	190	220	250	310	370	430	490	550	600	660	770
٩	NxØ	4*Ø18	4*Ø18	4*Ø18	4*Ø22	4*Ø26	4*Ø26	4*Ø26	4*Ø30	4*Ø30	4*Ø33	4*Ø36	4*Ø36	4*Ø36	4*Ø39
	NxM	4*M16	8*M16	8*M16	8*M20	8*M24	8*M24	12*M24	12*M27	16*M27	16*M30	16*M33	20*M33	20*M33	20*M36
	DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
49	FF	43	46	48	54	59	59	73	83	92	117	133	149	159	181
	ØL	125	145	160	190	220	250	320	385	450	510	585	610	670	795
PN	NxØ	4*Ø18	4*Ø18	4*Ø18	4*Ø22	4*Ø26	4*Ø26	4*Ø30	4*Ø33	4*Ø33	4*Ø36	4*Ø39	4*Ø39	4*Ø42	4*Ø48
	NxM	4*M16	8*M16	8*M16	8*M20	8*M24	8*M24	12*M27	12*M30	16*M30	16*M33	16*M36	20*M36	20*M39	20*M45
	DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
20	FF	43	46	48	54	57	57	64	71	81	92	102	114	127	154
15	ØL	120,7	139,7	152,4	190,5	215,9	241,3	298,5	362	431,8	476,3	539,8	577,9	635	749,3
#	NxØ	4*3/4"	4*3/4"	4*3/4"	4*3/4"	4*7/8"	4*7/8"	4*7/8"	4*1"	4*1"	4*1" 1/8	4*1"1/8	4*1"1/4	4*1"1/4	4*1"3/8
	NxM	4*5/8"	4*5/8"	4*5/8"	8*5/8"	8*3/4"	8*3/4"	8*3/4"	12*7/8"	12*7/8"	12*1"	16*1"	16*1"1/8	20*1"1/8	20*1"1/8
	DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600
0	FF	43	46	48	54	59	59	73	83	92	117	133	149	159	181
#300	ØL	127	149,2	168,3	200	235	269,9	330,2	387,4	450,8	514,4	571,5	628,6	685,8	812,8
#	NxØ	4*3/4"	4*7/8"	4*7/8"	4*7/8"	4*7/8"	4*7/8"	4*1"	4*1"1/8	4*1"1/4	4*1"1/4	4*1"3/8	4*1"3/8	4*1"3/8	4*1"5/8
	NxM	8*5/8"	8*3/4"	8*3/4"	8*3/4"	8*3/4"	12*3/4"	12*7/8"	16*1"	16*1"1/8	20*1"1/8	20*1"1/4	24*1"1/4	24*1"1/4	24*1"1/2


KV VALUE (PN16/ANSI150)



The flow factor "Kv" is defined as the flow of water, through a valve at temperatures between 5-40 °C, in cubic meters per hour (m³/h) at a pressure drop of 1 bar. This factor depends on the diameter of the valve, the shutter angle of aperture and its design.

$\overline{}$	10°	20°	30°	40°	50°	60°	70°	80°	90°
50	2	4	9	15	22	30	39	49	61
65	4	10	20	29	40	56	76	87	112
80	9	21	35	55	78	91	121	151	182
100	20	34	59	82	121	173	229	281	346
125	26	52	81	130	208	281	363	458	562
150	32	74	130	216	320	454	636	787	908
200	67	173	303	502	753	952	1298	1644	1903
250	83	216	398	692	952	1427	1990	2379	2855
300	143	311	580	865	1471	2206	2941	3720	4412
350	164	355	709	1125	1817	2509	3330	4152	5017
400	216	476	865	1644	2422	3460	4671	5882	6920
450	251	597	1081	2076	3114	4541	6488	7353	9083
500	389	744	1557	2595	4066	6055	7353	9948	12110
600	433	1125	2422	4239	7180	9342	12975	16868	18684

KV VALUE (PN40/ANSI300)



The flow factor "Kv" is defined as the flow of water, through a valve at temperatures between 5-40 °C, in cubic meters per hour (m³/h) at a pressure drop of 1 bar. This factor depends on the diameter of the valve, the shutter angle of aperture and its design.

	10°	20°	30°	40°	50°	60°	70°	80°	90°
50	2	4	9	15	22	30	39	49	61
65	4	10	20	29	40	56	76	87	112
80	9	21	35	55	78	91	121	151	182
100	20	34	59	82	121	173	229	281	346
125	26	52	81	130	208	281	363	458	562
150	32	74	130	216	320	454	636	787	908
200	56	134	247	389	588	779	995	1298	1557
250	81	208	368	631	865	1362	1903	2336	2725
300	121	268	484	800	1211	2054	2422	3244	4109
350	156	303	562	865	1471	2249	2855	3633	4498
400	173	381	779	1211	1990	2984	4671	4931	5969
450	238	519	952	1817	2768	4022	5623	7266	8045
500	303	666	1168	2163	3157	4887	6834	8304	9775
600	389	952	2076	3417	5493	8001	9602	12716	16003

TORQUE (PN16/ANSI150)

PN16/ANSI 150 (differential pressure in bar)														
VALVE SIZE SOFT SEATED							RE SAFE	DESIGN	ED	METAL SEATED				
INCH	ММ	Δp=5	Δp=1 0	Δp=1 5	Δp=2 0	Δp=5	Δp=1 0	Δp=1 5	Δp=2 0	Δp=5	Δp=1 0	Δp=1	Δp=2 0	
2"	50	27	30	32	33	43	46	47	48	53	59	60	61	
21/2"	65	29	31	33	36	45	48	49	50	58	61	62	64	
3″	80	30	33	35	41	48	50	51	53	61	64	66	67	
4"	100	37	44	50	59	65	71	74	77	82	90	94	97	
5"	125	52	59	64	83	77	89	91	97	87	109	116	123	
6"	150	62	77	90	97	94	100	106	114	120	127	135	146	
8"	200	96	135	142	164	144	159	176	194	184	202	224	247	
10"	250	157	199	239	277	211	247	290	323	269	314	370	411	
12"	300	217	284	351	418	265	341	416	500	336	433	531	635	
14"	350	327	424	541	687	470	617	763	911	598	784	971	1158	
16"	400	444	604	769	1009	587	822	969	1145	747	1046	1233	1457	
18"	450	613	822	1007	1308	822	1057	1291	1585	1046	1345	1644	2017	
20"	500	784	1238	1345	1879	939	1233	1585	1937	1366	1793	2305	2818	
24"	600	1366	1879	2348	2818	1699	2220	2764	3330	2092	2732	3373	4099	
	1 P								<u> </u>			20	21	

The torque values in the above table are in Nm.

TORQUE (PN40/ANSI300)

			P	N40/AI	NSI 300	(diffe	rential	pressui	re in ba	ır)				
VALVE	SIZE		SOFT S	SEATED		FI	FIRE SAFE DESIGNED				METAL SEATED			
INCH	ММ	Δp=2 5	Δp=3 5	Δp=4 0	Δp=5	Δp=2 5	Δp=3 5	Δp=4 0	Δp=5	Δp=2	Δp=3 5	Δp=4 0	Δp=5	
2"	50	42	43	44	45	54	57	58	59	68	71	73	74	
21/2"	65	43	45	46	47	57	59	60	62	71	74	75	79	
3"	80	46	49	50	52	61	63	64	71	77	79	80	89	
4"	100	68	72	75	82	90	96	106	112	112	121	132	140	
5″ 🔾	125	90	97	105	116	115	125	131	141	144	153	164	176	
6"	150	116	127	135	142	141	150	160	173	176	188	201	217	
8"	200	184	199	215	232	237	256	275	288	297	320	345	361	
10"	250	329	366	389	433	410	442	468	500	512	553	585	624	
12"	300	508	568	613	657	769	833	929	1089	961	1041	1161	1361	
14"	350	961	1161	1201	1321	1249	1388	1596	1734	1441	1601	1841	2001	
16"	400	1321	1441	1601	1761	1734	2012	2289	2428	2001	2321	2642	2802	
18"	450	1608	1921	2081	2241	2359	2740	3122	3435	2722	3163	3605	3963	
20"	500	2348	2519	2775	2989	3138	3736	4259	4632	2810	4536	5171	5625	
24"	600	3415	3842	4227	4525	4483	5379	6052	6724	5443	6532	7249	8165	

The torque values in the above table are in Nm.

TRIPLE OFFSET



TRIPLE OFFSET WORKING PRINCIPLES


Class Ansi 150/300 PN16/25/40


The center of rotation is offset from the sealing surface, from the central axis of the valve and also a third eccentricity due to the sealing seat elliptical conic section whose axisis inclined with respect to the pipe axis, this allows to have a good interference in the closing phase chafing or risks of bonding andt he use of materials resistant to high temperatures.

Triple off set butterfly valve mainly used for heavy duty application where a metal on metal seat is required.

TOP MOUNTING

Shaft finished depending on the requirements of implementing, on request may be made different than those shown above. Flanges in according with ISO 5211








TRIPLE OFFSET



	PARTS LIST
POS.	DESCRIPTION
1	BODY
2	DISC
3	STEM
4	BLINDPLUG
4 5 7	LAMELLAR SEAT
	UPPER BUSHING
	LOWER BUSHING
9	UPPER PACKING
10	ANTIBLOWOUT
	SCREW (ANTIBLOWOUT)
10.2	SPIRAL WOUND GASKET
	(ANTIBLOWOUT)
	ID PLATE
	RIVET
	RETAINING RING
	SOCKET HEAD CAP SCREW
	(BLIND PLUG)
16	SOCKET HEAD CAP SCREW
	(RET. RING)
	PIN (DISC/STEM)
	GLANDPLUG
20	STUD (GLAND PLUG)
	HEX. NUT (GLAND PLUG)
	WASHER (GLAND PLUG)
	SPIRAL WOUND GASKET
	(BLIND PLUG)
25	HEX. BOLT (BRACKET)
	WASHER (BRACKET)
	BRACKET
	HEX. BOLT (COMMAND)
	WASHER (COMMAND)
	HAND LEVER
	SPIRAL WOUND GASKET
	(SEAT)
	SPIRAL WOUND GASKET
	(RET. RING)

VALVE DIMENSION




DN	80	100	125	150	200	250	300	350	400	450	500	600
L1	125	150	165	185	215	240	285	300	340	380	410	495
L2	180	210	245	260	290	335	370	400	470	500	570	650
L3	25	30	30	40	45	45	60	60	75	75	90	100
DN	80	100	125	150	200	250	300	350	400	450	500	600
L1	150	160	180	195	235	260	300	330	370	400	445	525
L2	195	220	260	280	300	345	380	425	500	530	590	660
L3	25	30	30	40	45	45	60	60	75	75	90	120
DN	80	100	125	150	200	250	300	350	400	450	500	600
L1	165	180	215	220	260	300	335	390	415	450	490	565
L2	215	240	280	300	325	370	400	460	525	560	600	675
L3	35	40	40	50	60	60	75	75	90	90	120	150

FLANGE BOLTING DIMENSION

	DN	80	100	125	150	200	250	300	350	400	450	500	600
2	FF	48	54	59	59	73	83	92	117	133	149	159	181
2	ØL	160	190	220	250	310	370	430	490	550	600	660	770
PN	NxØ	4*Ø18	4*Ø22	4*Ø26	4*Ø26	4*Ø26	4*Ø30	4*Ø30	4*Ø33	4*Ø36	4*Ø36	4*Ø36	4*Ø39
	NxM	8*M16	8*M20	8*M24	8*M24	12*M24	12*M37	16*M27	16*M30	16*M33	20*M33	20*M33	20*M36
	DN	80	100	125	150	200	250	300	350	400	450	500	600
40	FF	48	54	59	59	73	83	92	117	133	149	159	181
2000	ØL	160	190	220	250	320	385	450	510	585	610	670	795
PN	NxØ	4*Ø18	4*Ø22	4*Ø26	4*Ø26	4*Ø30	4*Ø33	4*Ø33	4*Ø36	4*Ø39	4*Ø39	4*Ø42	4*Ø48
	NxM	8*M16	8*M20	8*M24	8*M24	12*M27	12*M30	16*M30	16*M33	16*M36	20*M36	20*M39	20*M45
	DN	80	100	125	150	200	250	300	350	400	450	500	600
0	FF	48	54	57	57	64	71	81	92	102	114	127	154
15	ØL	152,4	190,5	215,9	241,3	298,5	362	431,8	476,3	539,8	577,9	635	749,3
#	NxØ	4*3/4"	4*3/4"	4*7/8"	4*7/8"	4*7/8"	4*1"	4*1"	4*1" 1/8	4*1"1/8	4*1"1/4	4*1"1/4	4*1"3/8
	NxM	4*5/8"	8*5/8"	8*3/4"	8*3/4"	8*3/4"	12*7/8"	12*7/8"	12*1"	16*1"	16*1"1/8	20*1"1/8	20*1"1/8
Į	DN	80	100	125	150	200	250	300	350	400	450	500	600
0	FF	48	54	59	59	73	83	92	117	133	149	159	181
#30	ØL	168,3	200	235	269,9	330,2	387,4	450,8	514,4	571,5	628,6	685,8	812,8
#	NxØ	4*7/8"	4*7/8"	4*7/8"	4*7/8"	4*1"	4*1"1/8	4*1"1/4	4*1"1/4	4*1"3/8	4*1"3/8	4*1"3/8	4*1"5/8
	NxM	8*3/4"	8*3/4"	8*3/4"	12*3/4"	12*7/8"	16*1"	16*1"1/8	20*1"1/8	20*1"1/4	24*1"1/4	24*1"1/4	24*1"1/2
	DN	80	100	125	150	200	250	300	350	400	450	500	600
00	FF	54	64	78	78	102	117	140	155	178	200	216	232
009#	ØL	168,3	215,9	266,7	291,1	349,2	431,8	489	527	603,2	654	723,9	838,2
#	NxØ	4*Ø7/8"	4*1"	4*1"1/8	4*1"1/8	4*1"1/4	4*1"3/8	4*1"3/8	4*1"1/2	4*1"5/8	4*1"3/4	4-1"3/4	4*2"
	NxM	8*3/4"	8*7/8"	8*1"	12*1"	12*1"1/8	16*1"1/4	20*1"1/4	20*1"3/8	20*1"1/2	20*1"5/8	24*1"5/8	24*1"7/8

Kv VALUE (m³/h)



The flow factor "Kv" is defined as the flow of water, through a valve at temperatures between 5-40 ° C, in cubic meters per hour (m³ / h) at a pressure drop of 1 bar. This factor depends on the diameter of the valve, the shutter angle of aperture and its design.

	20°	30°	40°	50°	60°	70°	80°	90°
80	13	24	35	49	65	86	107	112
100	23	41	60	84	113	150	187	195
125	41	71	105	146	197	262	326	340
150	67	118	174	241	325	431	538	560
200	152	267	394	546	737	978	1219	1270
250	240	420	620	860	1160	1540	1920	2000
300	360	630	930	1290	1740	2310	2880	3000
350	552	966	1426	1978	2668	3542	4416	4600
400	768	1344	1984	2752	3712	4928	6144	6400
450	1044	1827	2697	3741	5046	6699	8352	8700
500	1320	2310	3410	4730	6380	8470	10560	11000
600	2040	3570	5270	7310	9860	13090	16320	17000

TORQUE


DN	Max. differential pressure Δp in bar for butterfly valve in closed position										
DN	10	16	20	25	30	35	40	45	50		
80	47	70	85	102	121	140	157	176	193		
100	79	114	137	165	194	223	251	280	309		
125	132	185	221	266	311	355	400	445	490		
150	274	373	439	521	603	685	768	850	932		
200	290	464	580	725	870	1015	1160	1305	1450		
250	488	750	925	1144	1363	1581	1800	2019	2238		
300	795	1107	1315	1575	1835	2095	2355	2615	2875		
350	1286	1817	2171	2614	3057	3500	3943	4386	4829		
400	1450	2230	2750	3400	4050	4700	5350	6000	6650		

The torque values in the above table are in Nm.



GENERAL INFORMATION Class PN 64

- New design
- High operating pressure
- Minimum F/F dimension
- Improved strenght
- Easy maintenance
- Connection NPT GAS




	DN	15	20	25	32	40
PN 64	L (mm)	11,5	14,5	15,5	22	26
PN	Ød (mm)	5,7	5,7	7	9	11
	F (N)	1	1,5	2,5	4,5	7

NON-RETURN VALVE



Non-return valve with screwed end connection; valve design with spring for installation in any position. Metal-to-metal seat. Application for liquids, gases and vapours (observe PED classification).

DOUBLE BLOCK AND BLEED



It includes options for high-pressure, critical processes, which are all manufactured in accordance with ASME standards.

GENERAL INFORMATION Class Ansi 150/300

Double Block and Bleed Butterfly Valves consists of two sets of triple offset butterfly valve components arranged in series, within a single integral valve body, to provide an inline separation cavity when both valves are in the closed position.

	DN	80	100	125	150	200	250	300	350	400
150	L1	150	160	180	195	235	260	300	330	370
	L2	195	220	260	280	300	345	380	425	500
ASME	L3	25	30	30	40	45	45	60	60	75
	FF	203	229	267	267	292	330	356	381	406
	DN	80	100	125	150	200	250	300	350	400
300	L1	165	180	215	220	260	300	335	390	415
	L2	215	240	280	300	325	370	400	460	525
ASME	L3	35	40	40	50	60	60	75	75	90
	FF	282	305	403	403	418	457	502	762	838







S.I.V.I.T. subjects all its products (also those marketed on request) to internal tests using equipment such as:



ITALCONTROL TEST BENCH



LASER MARKING MACHINE



HEXAGON MEASURING ARM

Certified as suitable to test valves up toclass 900 depending on the diameter.

It serves to mark all the details of the valves, detailing the drawing number, type of material, casting, etc

By which it is possible to measure the various parts of the valve to an accuracy of millimetre hundredths.







With the aim to work in high quality from materials up to the Certification, hereafter our Certificates List:

P.E.D. CERTIFICATE

UNI EN ISO 9001:2015

ATEX

FIRE SAFE API 607

FUGITIVE EMISSION













FIRE SAFE CERTIFICATES:

DN 100 BODY/DISC: **ASTM A182 F316L**

DN 100 **BODY/DISC:** ASTM A350 LF2

DN 100 BODY/DISC: ASTM B148 C95800 **DN 200** BODY/DISC: **ASTM A182 F316L** **DN 200** BODY/DISC: ASTM A350 LF2



REP 60-156-2020-IT	FIRESAFE	22/09/2020	Dalmine, Italy					
	Independent Third	Party Inspection Certificate						
Manufacturer identificat	ion							
Sede Legale / Unità Operativa	S.I.V.I.T. S.r.I.							
Head Office / Plant	Via Giuseppe Cavallo, 18 -	10078 Venaria Reale (TO)						
Product identification	1							
Type:	Valve type: SX							
Description	DOUBLE OFFSET BUTTERFLY VALVE - LUG TYPE DN100 ASME150 dwg SX0100015L							
Scope of Certification Prototype test with reference to the requirements of FIRE SAFE ISO 10497:2010 / API 607								
Reference standard	Test		Result					
ISO 10497 Ed. 07/10/2010								
API 6D Ed. XXIV, 2014								
API 607 Ed. VII, 2016	Fire safe test on double offs	et butterfly valve as per Type	SATISFACTORY					
API 6FA Ed. IV, 2018								
R5LAA2A0F1								
Test location:	S.I.V.I.T. S.r.I.							
	Body/Terminal Material: AS	TM A 182 F316L						
	Disc Material: ASTM A 182	F316L						
Packing Material and	Stem/shaft material: XM-19							
sealing Configuration	Seat Material: PTFE							
	Retaining ring: ASTM A 182	F316L						
		ocuments and requirements within spectory on DOUBLE OFFSET BUTTER						
Examination result:	Figure qualified: valves DN 100-125-150							
	Class 150, 300							
	UNI PN10	, PN16, PN25, PN40						
Test Report No.:	FIRE TEST REPORT N 200 Point 4.1.2	0057.3 / 200057.3-2 bi-directional test	in according to ISO 10497					
	ISO 10497 Ed. 07/10/2010							

ABS Group

Certificate no.: REP 60-157-2020-IT	Project no. FIRESAFE	Report date: 22/09/2020	Office: Dalmine, Italy						
	Independent Third	Party Inspection Certificate							
Manufacturer identificati	on								
Sede Legale / Unità	S.I.V.I.T. S.r.I.								
Operativa Head Office / Plant	Via Giuseppe Cavallo, 18 -	10078 Venaria Reale (TO)							
Product identification									
Type:	Valve type: SX								
Description	DOUBLE OFFSET BUTTERFLY VALVE - LUG TYPE DN100 ASME150 dwg SX0100015L								
Scope of Certification	Prototype test with reference	e to the requirements of FIRE SAFE	ISO 10497:2010 / API 607						
Reference standard	Test		Result						
ISO 10497 Ed. 07/10/2010									
API 6D Ed. XXIV, 2014									
API 607 Ed. VII, 2016	Fire safe test on double offs	set butterfly valve as per Type	SATISFACTORY						
API 6FA Ed. IV, 2018									
R5LAA2A0F1									
Test location:	S.I.V.I.T. S.r.I.								
	Body/Terminal Material: ASTM A 350 LF2								
	Disc Material: ASTM A 350	LF2							
Packing Material and	Stem/shaft material: 17-4Pl	4							
sealing Configuration	Seat Material: PTFE								
	Retaining ring: ASTM A 35	LF2							
		ocuments and requirements within spactory on DOUBLE OFFSET BUTTER							
Examination result:	Figure qualified: valves DN	100-125-150							
	Class 150	, 300							
	UNI PN10), PN16, PN25, PN40							
Test Report No.:	FIRE TEST REPORT N 20 Point 4.1.2	0056.3 / 200056.3-2 bi-directional tes	t in according to ISO 10497						
Test Procedure:	ISO 10497 Ed. 07/10/2010 API 6D Ed. XXIV, 2014 API 607 Ed. VII, 2016 API 6FA Ed. IV, 2018								

ABS Group S.I.V.I.T. S.r.I. API 6D Ed. XXIV. 2014 API 607 Ed. VII, 2016 API 6FA Ed. IV, 2018 Body/Terminal Material: B148 C9580 Disc Material: B148 C95800 Seat Material: PTFF Retaining ring: B148 C95800 According with the above documents and requirements within specified; Fire Safe Test has been conducted with satisfactory on DOUBLE OFFSET BUTTERFLY DN200 ASME150 igure qualified: valves DN 100-125-150 Class 150, 300 ISO 10497 Ed 07/10/201



Via Giuseppe Cavallo, 18 - 10078 Venaria Reale (TO) DOUBLE OFFSET BUTTERFLY VALVE - LUG TYPE API 6FA Ed. IV, 2018 Body/Terminal Material: ASTM A 182 F316L

Disc Material: ASTM A 182 F316L Seat Material: PTFF Retaining ring: ASTM A 182 F316L According with the above documents and requirements within specified; Fire Safe Test has been conducted with satisfactory on DOUBLE OFFSET BUTTERFLY DN200 ASME150 Figure qualified: valves DN 200 and larger Class 150, 300

ABS Group

API 6D Ed. XXIV. 2014 API 6FA Ed. IV, 2018 Body/Terminal Material: ASTM A 350 LF Disc Material: ASTM A 350 LF2

Seat Material: PTFF Retaining ring: ASTM A 350 LF2 According with the above documents and requirements within specified; Fire Safe Test has been conducted with satisfactory on DOUBLE OFFSET BUTTERFLY DN200 ASME150 Figure qualified: valves DN 200 and larger Class 150, 300

ISO 10497 Ed. 07/10/201





Contact Us

Phone Number



+39 011 062 02 30

Email Address



info@sivit-valves.com



commerciale@sivit-valves.com

Website



www.sivit-valves.com



S.I.V.I.T. SRL

for your attention!